




Pure in the structure, purely in the design, purely in the application. The POS-213 PurePOS is a POS system that provides the latest technology with a clear design and high functionality. User-oriented features allow for a scope that meets the needs.

The nearly frameless panel construction and the fantastic 2256 x 1504 DPI resolution enable a visual language that renders your interface and graphics razor-sharp.

Request our new POS-213 PurePOS.

All-in-One POS-213 PurePOS POS-213 Pure POS GT



1. 13.5" touch screen with thin bezel of only 7mm



2. Elegant and sleek design shared with customer display sister model MCM-213 PureTOUCH



3. Core I/O ports behind hinge cover



4. Cable management



5. Optional SCL-213 Scale Integration System to accept any load cell



6. Optional UCB-213 PureHUB Connectivity Box for extended connectivity





Model Name	POS-213 PurePOS	POS-213 PurePOS GT
Housing		
Material	Die-cast Magnesium-Aluminium (Panel PC), Plastic (Covers)	
Mount	VESA 75 + VESA Mount metal sheet 75 to 100	
Mainboard		
CPU	Intel Apollo Lake N4200 Quad-Core	Intel Kaby Lake Core i3-7100U / Core i5-7300U
GPU	Intel HD Graphics	
NVRAM	256KB	
System Memory	4GB up to 8GB	
Cooling	Passive (fanless)	
Display / Touch		
Display Size	13.5" TFT LCD with LED backlight	
Brightness	320 cd/m2	
Maximum Resolution	2256 x 1504	
Format	3:2	
Touch Screen Type	Projected Capacitive, Anti Glare Coated Glass	
Storage		
Primary Device Bay	M.2 2280 SSD 128GB (default) up to 512GB	
Main Unit External I/O Ports		
USB	2 x USB 2.0 (on I/O panel), 2 x USB 3.0 (on I/O panel), 1 x USB 2.0 (optional behind right side cover)	
LAN	1 x RJ-45 (10/100/1000 Mbit)	
Second Display	1 x USB Type-C (with screwlock) / 1 x Mini DisplayPort (with screwlock)	
DC in	1 x 24V 4Pin	
DC out to POS printer	1 x 24V 3Pin	
Link to Connectivity Box	1 x USB Type-C (with screwlock)	
Connectivity Box External I/O Ports		
USB	2 x USB (2 x USB 3.0)	
Powered USB	9 x Powered USB (1 x 24V + 8 x 12V)	
DC in	1 x 24V 4Pin	
DC out to Main Unit	1 x 24V 3Pin	
Serial/COM	2 x RS232 (optional)	
Link to Main Unit	1 x USB Type-C (with screwlock)	
Audio		
Speaker	1 x 1W	
Control/Indicator		
Power Button	LED Button (red light Off, green light On, green light flashing S3 Mode)	
Power Supply	External 90W/24V (Panel PC only) / 120W/24V (with UCB-213 PureHUB)	
Environment		
EMC & Safety	CE & FCC	
Operating Temperature	0~40° C	
IP	IP65 sealed front panel with touch screen	
Options		
Wireless Communication	802.11a/c (under left side of cover), Bluetooth 4.2, NFC, RFID 13.56MHz	
Connectivity	UCB-213 Connectivity Box	
Expansion	Module bay under right side cover (USB 2.0)	
Pen	Active stylus pen	
Dimension (W x H x D), Weight		
Panel PC only	307 x 224 x 38mm, 1.8kg	
Colour		
	Black with a silver frame	
OS Support		
	Windows 10, Linux CentOS	

Notes: Specifications are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product's appearance.

